

BRICK NET EKO'R

PH-NEUTRAL, COV-FREE CLEANER

FORMULATED FROM BIOBASED RAW MATERIALS

FACADE CLEANER, SPECIFICALLY ADAPTED TO BRIQUE FACADES
FACADES CLEANER EFFECTIVE - VISIBLE AND DURABLE RESULTS



P PRODUCT BENEFITS

- Formulated from biosourced raw materials
- VOC-free
- Visible and durable results
- pH neutral
- Formulated from biodegradable MP according to OECD standard
- Airless spray
- Without neutralizing the substrate (no efflorescence)
- Does not attack building materials
- Sprayable: Ideal for drone application = increased safety, time savings, uniform spraying, cost reduction



PACKAGING :

- 20 kg : pallet of 24 X 20 kg
- 5 kg : carton of 4 X 5 kg

A REAS OF APPLICATION

BRICK NET EKO'R is ideal for removing black atmospheric soiling from mineral surfaces. It is recommended for cleaning fragile materials such as bricks, concrete, porcelain, stoneware, glass paste, mignonettes, etc.

VOC-free, it is recommended for washing jobs where environmental constraints are important, particularly in high-traffic areas.

A PPLICATION

DILUTION : Ready to use, Nevers Dilute.

TOOLS : Roller, brush, airless or other sprayer, Compatible with spray drones

METHOD : Thoroughly homogenize the product before applying BRICK NET EKO'R.

Apply the product from bottom to top in a thick, greasy layer to the surface to be cleaned. Leave for 1 to several hours before rinsing from bottom to top with pressurized water. Repeat if necessary.

APPLICATION TIME : One to several hours. We advise applying in the evening and rinsing the following day.

APPLICATION TEMPERATURE : From 5 to 50°C. Efficacy is reduced at extreme temperatures

CLEANING OF TOOLS : Clean tools in water immediately after use.



SCALP[®] SAS 

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.

APPLICATION RATE: From 100 to 200 g/m² according to surface porosity.*

STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

CARACTERISTICAS FISICOQUIMICAS

- | | |
|---|--|
| <ul style="list-style-type: none">• Aqueous product in thixotropic gel form• Slightly yellowish• Density : 1.1 +/- 0.03 g /cm³ at 20°C | <ul style="list-style-type: none">• pH : 7• Not frost resistant, but effects reversible• Flash point : Non-flammable |
|---|--|

APPLICATION PRECAUTIONS

PROTECTION OF SURFACES Does not require any protection, clean possible splashes quickly with a cloth.

PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, wash with water. Wear PVC gloves. Wear a helmet with face shield for spray application. Wear goggles for brush application. Wear suitable coveralls (waterproof).

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP SAS, an EcoVadis-certified company – the certification is awarded to the company, not the product.

SCALP[®] SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.