

SCALP PROTEC MAGIC

**SINGLE-COMPONENT, PERMANENT ANTI-GRAFFITI PROTECTION
ALLOWS FOR MORE THAN 100 GRAFFITI REMOVALS FROM A SINGLE
SURFACE**



P PRODUCT BENEFITS

★★★★★
**TOP
- QUALITY -**



**ALL
SURFACES**

- All surfaces
- Allows for more than 100 graffiti removals
- Excellent UV- and abrasion-resistance: does not yellow
- Extremely easy to apply
- Single-component product
- Suitable for indoors and outdoors
- Graffiti removal by friction using SCALP SENSITIVE SURFACE CLEANER or WIPES EXPRESS 70 specially for graffiti



PACKAGING :
• 5 L: 4 x 5 L pack

A AREAS OF APPLICATION

SCALP PROTEC MAGIC is an extremely resistant permanent and single-component anti-graffiti protection. Graffiti can be very easily removed by friction using special cleaners, SCALP SENSITIVE SURFACE CLEANER or WIPES EXPRESS 70 specially for graffiti. Very good adhesion and no peeling on all surfaces.

A APPLICATION

1. DILUTION: Ready to use.

2. APPLICATION EQUIPMENT: Short-bristle roller suitable for solvent products.

3. OPERATING PROCEDURE:

A) APPLICATION OF PROTECTION: Thoroughly mix SCALP PROTEC MAGIC, then apply a single coat to the substrate to be treated. Avoid any excess product, as this can cause drippings and leave marks on the surface. Apply SCALP PROTEC MAGIC to clean and dry surfaces.

B) GRAFFITI REMOVAL:

SCALP SENSITIVE SURFACE CLEANER: Apply SCALP SENSITIVE SURFACE CLEANER to the graffiti in small, circular motions, then leave to work. Wipe with a cloth. Repeat operation if necessary.

WIPES EXPRESS 70 SPECIALLY FOR GRAFFITI: With a light rub, a simple anti-graffiti wipe removes unwanted paints and graffiti.



SCALP SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.

4. APPLICATION TIME: 10 to 20 minutes.

5. APPLICATION TEMPERATURE: 5 °C to 30 °C in dry weather.

6. CLEANING OF TOOLS: Clean tools with water immediately after use.

7. YIELD: 150 to 250 g/m² depending on the type of surface*.

8. STORAGE: Store product in frost-free premises, sheltered from bad weather and direct sunlight.

*Yield information is only provided as a rough guide. This information helps assess and calculate the quantity needed for work-sites. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

PHYSICO-CHEMICAL FEATURES

- | | |
|---|----------------------|
| • Single-component product | • pH: not applicable |
| • Appearance: slightly viscous liquid | • VOC: 240 g/L |
| • Density: 0.85 g ± 0.05 g/cm ³ at 20 °C | • Flash point: 62 °C |

A APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Only apply SCALP PROTEC MAGIC to the surface to be protected.

2. PROTECTION OF PERSONS: Avoid contact with eyes and skin. Wear PVC gloves and safety goggles.

Important: The contents of this document stem from our experience of the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each substrate (wear and tear, alteration of the whole surface and / or properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the application procedure, in order to ensure that there is no alteration. Professional product: dangerous, follow the precautions for use. Wear personal protective equipment (PPE) and refer to the Safety Data Sheet (SDS).



SCALP SAS, an EcoVadis-certified company - the certification is awarded to the company, not the product.

SCALP[®] SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.