

COMPLEMENTARY PRODUCT RANGE

SCALP DECOL'PAPIER

HIGH PERFORMANCE TENSIDE-BASED PRODUCT FOR STRIPPING
WALLPAPERS, POSTERS OR ADVERTISING POSTERS



P PRODUCT BENEFITS



- High power wetting agent
- Can be sprayed
- Faint odour
- Fast
- Non-flammable
- Highly concentrated product, can strip 250 to 300 m² litre.
- Less restrictive than steam strippers and more economical (very high application rate)
- Easily biodegradable
- VOC-free



PACKAGING :

- Drum of 200 L
- 20 L: pallet of 24 X 20 L
- 5 L: carton of 4 X 5 L
- 1 L: carton of 10 X 1 L

A AREAS OF APPLICATION

SCALP DECOL'PAPIER removes all types of wallpapers. It easily dissolves all the adhesives frequently used on the market.

A APPLICATION

1. DILUTION:

- common wallpapers: 50ml for 5L of water
- vinyl papers: 100ml for 5L of water

2. TOOLS: Roller, sprayer, wallpaper brush, sponge

3. METHOD: Thoroughly homogenize SCALP DECOL'PAPIER. Dilute according to wallpaper type and mix thoroughly. Scratch paper that is too thick to facilitate product penetration. Apply SCALP DECOL'PAPIER generously. Leave to act for 10 minutes to ½ hour, then remove the paper with a spatula, knife or by hand.

4. APPLICATION TIME: From 10 minutes to ½ hour.

5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures.

6. CLEANING OF TOOLS : Clean tools in water immediately after use

7. APPLICATION RATE: From 250 to 300 ml /m².*

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.



SCALP[®] SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.

PHYSICOCHEMICAL PROPERTIES

- Water-based product
- Colourless liquid
- Density : 1 to 1,08 +/- 0.03 g /cm³ at 20°C
- pH : 7 to 8
- Not frost resistant, but effects reversible
- Flash point : N/A

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Avoid contact with surfaces that are not to be removed.

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear gloves and safety goggles.

The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP SAS, an EcoVadis-certified company – the certification is awarded to the company, not the product.

SCALP[®] SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.