

WATER-REPELLENT / OIL-REPELLENT RANGE



SCALP® SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.

SCALPFUGE OM 70

SOLVENTED WATER REPELLENT - NON-SILICONE, NON-FILM FORMING, ORGANIC-METALLIC COMPOUNDS BASED.



PRODUCT BENEFITS



- Highly sophisticated product
- SCALPFUGE OM 70 can be painted
- Micro-porous, facilitating the free exchange of water vapour
- Contains no silicone
- Can be sprayed
- Easy and rapid impregnation of material pores
- Produces a beading effect



PACKAGING :

- In container of 200 litres
- 30 litres: pallet of 22 X 30 litres

AREAS OF APPLICATION

SCALPFUGE OM 70 is designed for the water repellent treatment of stones, plaster, hydraulic coatings, cement, concrete, brick, marble, tiles, slates, fibro-cement.

APPLICATION

1. DILUTION : Ready to use. Never dilute.

2. TOOLS : Natural fibre roller, manual sprayer.

3. METHOD : Mix the product well before use; apply to the surface to be treated from the base upwards until total saturation of the surface. Renew the operation a second time after about 20 minutes. Avoid overuse of the product, which could leave coloured traces on the surface. Apply the product to clean and dry surfaces.

4. APPLICATION TIME : This is a permeating solution. Water repellent treatment will be effective immediately after the evaporation of solvents (after about 72 hours).

5. APPLICATION TEMPERATURE : From 5 to 50°C. Efficacy is reduced at extreme temperatures.

6. CLEANING OF TOOLS : Clean tools in white spirit immediately after use

7. APPLICATION RATE : According to materials and their porosity: about 300 ml/m² for both coats.*

8. STORAGE: Store the product in a cool dry place and out of direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|---|---|
| <ul style="list-style-type: none">• Solvated product• Transparent, colourless liquid• Density : 0.78 +/- 0.03 g /cm³ at 20°C | <ul style="list-style-type: none">• pH : N/A• Frost resistant• Flash point : 36°C |
|---|---|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Do not apply SCALPFUGE PS 86 to organic coatings (Thick and medium plasticized paints, etc.). Protect surfaces that are not to be water repellent treated (glass, PVC, etc.).

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear PVC gloves. Wear a helmet visor to shield the face while spraying. Wear safety goggles when applying with a roller. Wear suitable overalls (waterproof). Work in well-ventilated conditions Do not smoke.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP SAS, an EcoVadis-certified company - the certification is awarded to the company, not the product.

SCALP[®] SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.