

#### **MOTORNET**

**ENGINE-GREASE REMOVER** 









- Does not cause metal corrosion or superficial damage to insulating varnishes.
- Frost-proof.
- Easy to use.



#### **PACKAGING:**

- 1,000 L container
- 210 L barrel
- 20 L: 24 x 20 L pallet
- 5 L: 96 x 5 L pallet

## A REAS OF APPLICATION

SCALP ENGINE CLEANER is a cleaner, grease remover and emulsifier. It removes oil and grease from mechanical parts and painted or non-painted metallic surfaces. It removes grease from engine parts.

It is used as an engine shampoo.

## APPLICATION

- **1.DILUTION**: Product is ready to use.
- **2.APPLICATION EQUIPMENT:** Brush.
- **3.OPERATING PROCEDURE**: Can be used as is, applied with a brush, sprayed onto the part to be cleaned or by immersion.
- **4.APPLICATION TEMPERATURE**: 5 °C to 50 °C. Effectiveness is reduced at extreme temperatures.
- **5. TOOL CLEANING:** Clean tools with water straight after application.
- 6. YIELD: 100 to 200 ml / m<sup>2</sup> depending on the way in which it is used.
- 7. STORAGE: Store product in frost-free premises, away from the elements and direct sunlight. Do not store at temperatures < 5 °C.
- \* Yield information is only provided as a rough guide. This information is useful to determine the amount needed for the work. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

#### **PHYSICO-CHEMICAL FEATURES**

- Water soluble (milky emulsion)
- Light amber liquid
- Density: 0.770 g / cm3 at 20 °C
- Free of chlorinated solvent
- Frost-proof
- Corrosiveness: None on metals, rubber and plastics

# A PPLICATION PRECAUTIONS

- 1. PROTECTION OF SURFACES: Do not apply product to surfaces that are very hot or have been exposed to the sun.
- 2. PROTECTION OF PERSONS: Wear gloves and safety goggles. Avoid contact with eyes. In the event of splashing, rinse with water.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and / or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs.







Tél.: +33 (0)1 48 48 39 76 Fax: +33 (0)1 48 49 80 36

