

SCALP WATERPROOF BARRIER

HYBRID, IMPERMEABLE MEMBRANE
COVERS AND REPAIRS CRACKS IN ALL SUBSTRATES



ALL
SURFACES

★★★★★
TOP
-QUALITY-



PACKAGING:

- 5 KG: 4 x 5 KG pack
- 750g: 24 x 750g pack

PRODUCT BENEFITS

- Resists light and weather
- Repairs cracks
- Reinforces joints
- Forms a watertight film on roofs, terraces...
- High elasticity
- Does not need to be coated
- Does not crack
- Ideal for exterior use: resists UV, rain, temperature variations, snow, etc.
- Protects against water infiltration
- Durable protection
- Non-sticky
- Low VOC content

AREAS OF APPLICATION

SCALP WATERPROOF BARRIER is a high-quality waterproof hydride membrane in the form of a fibrous paste, offering excellent adhesion without being sticky. This innovative membrane is designed to meet the need for protection against water and weather. Thanks to its advanced features, it offers excellent light and weather resistance, while repairing existing cracks and reinforcing joints.

SCALP WATERPROOF BARRIER stands out for its ability to form a waterproof film on roofs, gutters, terraces, etc., effectively protecting surfaces against water infiltration. Its high elasticity enables it to adapt to structural movements without cracking or degrading, ensuring lasting protection in a wide range of environmental conditions. This makes it ideal for outdoor use, where it is resistant to UV rays, rain, snow and temperature variations.

APPLICATION

1. DILUTION: Ready-to-use product. No need for prior dilution.

2. APPLICATION EQUIPMENT: Brush.

3. OPERATING PROCEDURE: SCALP WATERPROOF BARRIER is easy to use. Simply clean the surface to be treated of all dust, mud, dead leaves, etc., and blot dry. Then apply the membrane directly to the substrate using a brush or paintbrush. After a drying time of 12 to 24 hours, the treated surface can be covered if necessary.

4. DRYING TIME: 12 to 24H depending on environmental conditions and humidity.

5. APPLICATION TEMPERATURE: 5 to 40 °C. Less effective at extreme temperatures.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

6. TOOL CLEANING: Clean tools with water immediately after use.

7. YIELD: 1-1.5 kg/m²

8. STORAGE: Store product in frost-free premises, sheltered from bad weather, sources of incandescence and direct sunlight.

* Yield information is only provided as a rough guide. This information helps assess and calculate the quantity needed for work-sites. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

PHYSICO-CHEMICAL FEATURES

- Viscosity: paste
- Density: 1.2 ± 0.03 g/cm³ at 20 °C
- Dry extract: 74 +/- 2% (by weight)
- Finish: matt
- Resistance to saponification: optimal
- Dry to the touch: 2-6 hours

APPLICATION PRECAUTIONS

PROTECTION OF PERSONS: Avoid contact with eyes and skin. Wear PVC gloves and safety goggles. In case of contact, wash with water

Important: The contents of this document stem from our experience of the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each substrate (wear and tear, alteration of the whole surface and / or properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the application procedure, in order to ensure that there is no alteration. Professional product: dangerous, follow the precautions for use. Wear personal protective equipment (PPE) and refer to the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.