



### **SCALP GRAFFITI REMOVER**

SUPER CLEANER FOR INTENSIVE GRAFFITI REMOVAL FROM WALLS, FAÇADES AND CONSTRUCTION WORKS

# P PRODUCT BENEFITS









- Ideal for maintenance and intensive urban cleaning of graffiti
- Ideal for the constant cleaning of graffiti
- Essential for the technical services of municipalities
- Suited to vertical surfaces
- Fast-acting
- Effective
- Helps remove all kinds of graffiti: varnishes, lacquers, inks, spray paints, marker pens etc.
- Does not leave any shadows or ghosting after cleaning



#### **PACKAGING**

- 20 kg: 24 x 20 kg pallet
- 5 kg: 4 x 5 kg pack

# A REAS OF APPLICATION

SCALP GRAFFITI REMOVER is designed to remove all types of graffiti from rough and porous surfaces, like natural stone, concrete, cement, granite, marble, slate, wood etc. (test first).

## APPLICATION

- 1. DILUTION: ready-to-use.
- 2. APPLICATION TOOLS: roller or paint brush.
- 3. OPERATING PROCEDURE: Mix thoroughly. Apply SCALP GRAFFITI REMOVER liberally onto graffiti, from bottom to top. Leave to work for 5 to 10 minutes, based on weather conditions. Rinse off with pressurised water.

<u>CAUTION:</u> On sandstone or limestone surfaces, it is recommended not to apply strong pressure to avoid damaging the surface.

- 4. APPLICATION TIME: 5 to 10 minutes.
- <u>5. APPLICATION TEMPERATURE</u>: 0 °C to 40 °C. Efficacy is reduced at extreme temperatures.
- **<u>6. TOOL CLEANING</u>**: Tools must be cleaned with water straight after use.
- **7. YIELD**: About 300 g / m<sup>2\*</sup>.
- **8. STORAGE**: Store product in frost-free premises, away from the elements and direct sunlight.

\*Yield information is only provided as a rough guide. This information is useful to work out the amount needed for the project. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

### **PHYSICO-CHEMICAL FEATURES**

Appearance: viscous liquid

Colour: yellow / brown

Density:  $1.035 \pm 0.03 \text{ g} / \text{cm}^3 \text{ at } 20 \text{ °C}$ 

pH: > 11.5Frost-proof

Flash point: 2 °C

## A PPLICATION PRECAUTIONS

**1. PROTECTION OF SURFACES**: Avoid prolonged application on plastic or painted surfaces and organic coatings to prevent damage.

**2. PROTECTION OF PERSONS**: No smoking. Wear PVC gloves and safety goggles when applying with a roller or brush. Highly flammable and corrosive product. Do not inhale vapours and mists. Wear gloves, goggles or face protection. Work in a well-ventilated area, away from heat and all sources of ignition. If splashed onto skin or into eyes, immediately rinse with plenty water, keeping eyelids apart. Immediately see a doctor.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and / or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs. Professional product: dangerous, follow application precautions. Wear personal protective equipment (PPE) and refer to the safety data sheet (SDS).





