

### **DEGRIP'EXPRESS**



SUPER PENETRATING OIL, DEGREASER, EMULSIFIER, MOISTURE REPELLENT, OF 100 % NATURAL ORIGIN

DEGRIP'EXPRESS REPELS MOISTURE AFTER APPLICATION AND PROVIDES WATER RESISTANCE







- Formula is of 100% natural origin
- Compatible with all materials
- Readily biodegradable



- Very versatile
- Fast-acting
- NSF-certified product
- Low VOCs





### PACKAGING:

- 400 ml: 12 x 400 ml cardboard box
- 400 ml: 84 x 400 ml pallet





# <u>Multi-purpose, moisture-repelling, anti-corrosion, cleaning, lubricating and penetrating oil with Lu-4 straw</u>

Aerosol can with a two-position straw that enables wide-angle or accurate spray, depending on the specific application.

DEGRIP'EXPRESS lubricates mechanical parts thanks to its high degree of penetration, leaving a light, oily film that protects against water and moisture and their corrosive impact. DEGRIP'EXPRESS protects against oxidation and all forms of corrosion, even in the most extreme conditions.

It prevents squeaking and forms a protective and insulating film.

DEGRIP'EXPRESS prevents dust and grime build-up on metal parts. This product has been specially designed to quickly and effectively penetrate assembled parts that have become stuck from the products of oxidation.

The strong adherence of DEGRIP'EXPRESS to metal, as well as its lubricating properties, ensure that loosened parts work constantly. One of the main components of DEGRIP'EXPRESS is an active and permanent lubricant that is free of silicone and lanolin and contains no other additive that attracts dust or dirt. Parts and mechanisms are thus properly lubricated.

# A PPLICATION

- 1. DILUTION: Ready-to-use product.
- 2. APPLICATION EQUIPMENT: The two-position sprayer is the application tool.
- 3. APPLICATIONS: Mechanical parts, locks, industry, maintenance, bike chains, engine parts.
- 4. OPERATING PROCEDURE: Shake aerosol can well before use. For a wide-angle spray, leave the straw alongside the aerosol can. For an accurate spray, lift up the straw. Spray onto the parts to be treated. Wait a few moments and repeat the procedure if the parts are badly corroded. If necessary, manipulate the part to be lubricated. As a moisture-repelling treatment: clean surfaces. Spray. Wait until completely dry before putting the parts back to work.
- 5. STORAGE: Store product in frost-free premises, away from the elements and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and any other source of ignition. Do not store at temperatures >50 °C.
- **6. FEATURES:** Gross volume: 400 ml Propellant: butane / propane.
- \* Yield information is only provided as a rough guide. This information is useful to work out the amount needed for the project. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

#### PHYSICO-CHEMICAL FEATURES

Light brown liquid

pH: 6.7

Flash point: <0 °C

## A PPLICATION PRECAUTIONS

PROTECTION OF PERSONS: Avoid open flames and agitation. No smoking. Avoid contact with skin and eyes, as well as inhaling spray fumes and mist. Wear PVC gloves. Wear safety goggles. If swallowed, do not induce vomiting, but immediately see a doctor and show them the packaging or label.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and / or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs. Professional product: dangerous, follow application precautions. Wear personal protective equipment (PPE) and refer to the safety data sheet (SDS).







Tél.: +33 (0)1 48 48 39 76 Fax: +33 (0)1 48 49 80 36