

DEROX 320

CLEANER AND DEGREASER OF METALS (ZINC, ALUMINIUM, GALVA)
PRIOR TO PAINTING



PRODUCT BENEFITS



- Fast and very effective
- Highly versatile
- Concentrated
- Faint odour
- Low VOC content (14.6g/L)



PACKAGING :

- 25 kg: pallet of 24 X 25 kg
- 6 kg: carton of 4 X 6 kg
- 1.2 kg: carton of 10 X 1.2 kg

AREAS OF APPLICATION

DEROX 320 prepares metals (zinc, aluminium, galva) before painting. This stripping acid compound improves the porosity of metals to promote adhesion. This product is a degreaser for all metal surfaces prior to painting (respect metal painting systems, whether anti-corrosion or otherwise)..

APPLICATION

1. DILUTION: Use pure or diluted:

- Aluminium: 100%
- Zinc: 50%
- Galvanised steel: 50%.

2. TOOLS: Paintbrush, brush, roller or by dipping.

3. METHOD: Apply the product onto the surface and then leave it to act. Scrub with a brush and thoroughly rinse the surface with water.

4. APPLICATION TIME: 5-10 minutes or more depending on the desired roughness.

5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE: 150 g/m² after dilution*.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

8. STORAGE : Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|---|---|
| • Highly concentrated | • pH : 1 |
| • Colourless liquid | • Not frost resistant, but effects reversible |
| • Density : 1.2 +/- 0.03 g /cm ³ at 20°C | • Flash point : Non-flammable |

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces that do not require cleaning (paint, marble, limestone, glass, metal and surrounding vegetation). If in doubt, test a small area first. Do not apply DEROX 320 to calcareous materials.

2. PROTECTION OF PERSONS: This product is a mixture of mineral acids. It is corrosive to the skin and can cause severe burns. In case of skin contact, wash immediately with water. Wear full chemical protection suit. Use full-face safety goggles to protect against splashes. Wear PVC gloves.

Important: The contents of this documentation are based on our experience with the product. We cannot be held responsible for its use in any particular case. In view of the specific characteristics of each surface (wear, alteration of completeness and/or properties, chemical composition, etc.) and to avoid any deterioration of the surface to be treated, it is essential to carry out a test application of Scalp on a small area to be treated, in accordance with the application procedure, to ensure that no alteration has occurred. Professional product: dangerous, observe safety precautions. Wear Personal Protective Equipment (PPE) and consult the Material Safety Data Sheet (MSDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.