

NEUTRAL DA 66



HIGH PERFORMANCE NEUTRALIZER BRIGHTENER FOR WOOD GREYED
BY WEATHER OR CLEANED BY AN ALKALINE REMOVER



P PRODUCT BENEFITS



- Fast
- Can be sprayed
- Effective on all types of wood
- Can be repainted immediate
- Requires a light rinsing
- VOC free



PACKAGING :

- 20 kg: pallet of 24 X 20 kg
- 5 kg: carton of 4 X 5 kg
- 1 kg: carton of 10 x 1 kg

A AREAS OF APPLICATION

This product is designed to brighten all types of wood blackened by weather or time and to neutralize after alkaline scouring

A APPLICATION

1. DILUTION: Dilute in 50% of water or use pure according to the state of the surface

2. TOOLS: Brush, natural fibre roller, sprayer (spray).

3. METHOD: The surface to be treated must be dust-free and dry. Thoroughly homogenize the product and apply to the surface (can also be used as a brightening neutralization bath: polyethylene tank). Leave to act for 10 to 15 minutes at most, then rinse with a high-pressure cleaner at 30 to 40 bar, spraying from a distance of around 30 cm from the surface to avoid damaging the wood fibres, or use a nylon brush with hard bristles and rinse with a water jet.

4. APPLICATION TIME: Results almost instantaneous.

5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures.

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE: Variable according to the type of wood (from 150 g to 300 g/m²).*

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

PHYSICOCHEMICAL PROPERTIES

- Fluoride salts based product in water phase
- Colourless liquid
- Density : 1.05 +/- 0.03g/cm3 at 20°C
- pH : 1
- Not frost resistant, but effects reversible
- Flash point : N/A

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Do not apply to siliceous and limestone materials. Do not apply to glass

2. PROTECTION OF PERSONNEL: Wear PVC gloves. Wear a helmet with face shield for spray application. Wear goggles for roller or brush application. Wear suitable coveralls (waterproof). Avoid contact with eyes and skin. In case of contact, wash hands and eyes immediately with plenty of water. If irritation persists, seek medical advice immediately.

The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.