

SCALPEX AE NW

HIGH PERFORMANCE SPRAY STRIPPER
IDEAL FOR INDOOR AND OUTDOOR.



PRODUCT BENEFITS



ALL
SURFACES

- Effective on a wide variety of substrates
- Fast-acting
- Easy-to-apply aerosol
- Compact foam, excellent adhesion to substrate
- Indispensable for difficult access



PACKAGING :

- 500 ml : pack of 12 X 500 ml

AREAS OF APPLICATION

SCALPEX AE NW is a blend of solvents designed for stripping a wide variety of paints (Acrylic, Glycerol, Pliolite, Alkyd, etc.), glues, inks, varnishes, woodstains and graffiti from a wide range of surfaces (wood, iron, stone, bricks, glass paste, mineral plaster, etc.). Graffiti removal. In-depth stripping of paint, ink and varnish. Destruction of joints. Can be used on bodywork, grilles, doors, floors and walls.

APPLICATION

1. DILUTION : Ready to use.

2. APPLICATION EQUIPMENT : No need.

3. METHOD : Homogenize: shake SCALPEX AE NW well before application. Spray from a distance of around 20 cm onto the surfaces to be treated, allowing sufficient time for thorough coverage. Allow to work for a few minutes, depending on the thickness of the paint to be stripped. The appearance of vermicules and blisters indicates the effectiveness of the product. Remove stripped paint with a spatula. Stripped areas can be cleaned with a dry cloth, spatula or wire brush. After each use, purge the can upside down.

4. APPLICATION TIME : From 1 to 10 minutes according to the type of coating.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

5. APPLICATION TEMPERATURE : From 5 to 50°C. Efficacy is reduced at extreme temperatures.

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE : About 120ml / m2 according to coating.*

8. STORAGE : Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|--|--------------------|
| • White foam | • pH : 7 |
| • Gas: Butane/ Propane | • Frost resistant |
| • Density: 1.18 +/- 0.03 g/cm ³ at 20°C | • Highly flammable |

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES : Do not apply to PVC, rubber, plastic tiles or polystyrene

2. PROTECTION OF PERSONNEL : Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear PVC gloves and protective eyewear. Do not inhale fumes.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear, alteration of the entire surface and/or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that some of the SCALP product be tested on a small area to be treated, by following the procedure for application, and thereby ensuring that there is no alteration. Professional product: dangerous, follow application precautions. Wear personal protective equipment (PPE) and refer to the safety data sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.