

SCALPEX NW NG

UNIVERSAL, GEL SUPER-STRIPPER FOR A VARIETY OF
PAINTS, VARNISHES, TAGS AND GLUES



PRODUCT BENEFITS



ALL
SURFACES

- Ideal for painters
- Does not contain dioxolane
- Non-drip, low consumption
- Proven effectiveness on all organic substrates
- Ideal viscosity, suitable for vertical surfaces
- Ultra-fast action
- New-generation product
- No rinsing required
- Ideal for stripping lead and asbestos paint



PACKAGING :

- 20 L: 24 x 20 L pallet
- 5 L: 4 x 5 L pack
- 750 ml: 24 x 750 ml pack

AREAS OF APPLICATION

SCALPEX NW NG is designed for stripping stains, paints and varnishes from surfaces such as: wood, woodwork, iron, zinc, galvanised metal, stone and concrete.

APPLICATION

- 1. DILUTION** : Ready to use.
- 2. APPLICATION EQUIPMENT** : Natural fibre or graining brush..
- 3. METHOD** : Shake well before use, apply thickly, leave to work, then scrape off with a scraper or jack plane. Avoid applying to wet surfaces.
- 4. APPLICATION TIME** : : From 20 minutes, depending on climatic conditions and coating. Never allow product to dry.
- 5. APPLICATION TEMPERATURE** : From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- 6. CLEANING OF TOOLS** : Tools must be cleaned with water as soon as possible after application.
- 7. APPLICATION RATE** 300 - 600 ml/m² depending on the coating. *
- 8. STORAGE** : Store the product in frost-free premises, away from the elements, incandescent light sources and direct sunlight.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|--|----------------------------|
| • Solvent-based product | • pH : >4 |
| • Colourless to slightly yellowish gel | • Frost-proof |
| • Density: 0,96g $\pm$ 0.05g/cm ³ in 20°C | • Viscosity > 3 000 m Pa.s |

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES : Do not apply to PVC, rubber, plastic tiles or polystyrene

2. PROTECTION OF PERSONNEL : Avoid contact with eyes and skin. Wear safety goggles. In case of contact, immediately wash hands and eyes with water. Do not inhale vapours. Wear PVC or latex gloves of the following type: GOLDEX LATEX 3130 or PVC535K, or PVA or nitrile butyl rubber gloves. When using the product in an enclosed, non-ventilated area, a breathing apparatus, equipped with a Category-A vapour and gas filter, is recommended.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear, alteration of the entire surface and/or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that some of the SCALP product be tested on a small area to be treated, by following the procedure for application, and thereby ensuring that there is no alteration. Professional product: dangerous, follow application precautions. Wear personal protective equipment (PPE) and refer to the safety data sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.