

#### **SCALP PROTECT WA 67**

MATT FINISH, COLOURLESS RENEWABLE, SACRIFICIAL ANTI-GRAFFITI PROTECTION - ECOLOGICAL VEGETAL WAX BASED.



### P PRODUCT BENEFITS





- Very easy to apply
- Versatile (very wide variety of surfaces)
- Micro-porous and water repellent product
- Contains no solvents
- Effective for inside and outside
- Does not yellow
- Odourless
- Invisible film (according to surface)
- Resists U.V.
- Can be sprayed
- Removal of graffiti with hot water (90°C) and under pressure



#### **PACKAGING:**

20 kg : pallet of 24 X 20 kg5 kg : carton of 4 X 5 kg

# A REAS OF APPLICATION

PROTECT SCALP WA 67 is designed for anti-graffiti protection of all surfaces with the exception of non anti-corrosion treated metallic surfaces.

### APPLICATION

- 1. DILUTION: Ready to use.
- 2. Tools: Roller (lacquer), sprayer (airless spray gun).
- 3. METHOD: Mix the product well before application. Apply SCALP PROTECT WA 67 to a clean dry surface in two crossed coats (at about 2 hours interval according to outside temperature). Avoid over-colouring and overuse. Removal of the graffiti: Graffiti will be effectively removed with hot water (90°C at 30 bar minimum). The protection and the graffiti will be removed; therefore the protection will need to be renewed.
- 4. APPLICATION TIME: About 2 hours according to climatic conditions and surface.

- <u>5. APPLICATION TEMPERATURE</u>: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- 6. CLEANING OF TOOLS: Clean tools in water immediately after use.
- 7. APPLICATION RATE: From 150 to 200 g/m² per coat according to surface porosity.\*
- **8. STORAGE:** Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.
- \* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

#### CARACTERISTICAS FISICOQUIMICAS

- Vegetable wax based product in emulsion
- Milky liquid
- Density: 0.96 +/- 0.03 g/cm³ at 20°C
- pH:9
- Not frost resistant
- Flash point : N/A

# A PPLICATION PRECAUTIONS

- 1. PROTECTION OF SURFACES: Avoid contact with all surfaces that are not to be protected.
- **2. PROTECTION OF PERSONNEL**: This product is not dangerous, but avoid contact with eyes and skin. In case of contact, wash with water. Wear PVC gloves and protective eyewear.

**Important**: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



