

SCALP RENOV'EXPRESS

SUPER CLEANER AND FACE SCRUBBER
QUICK FLASH EFFECT



PRODUCT BENEFITS



- Immediate effectiveness: 15 min to 2h
- High-powered product with long-lasting effect
- Very easy to apply
- Sprayable (effective rinsing of sprayer after use)
- No rinsing (except if repainting or waterproofing)
- VOC-free



PACKAGING :

- In containers of 200 litres
- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

AREAS OF APPLICATION

SCALP RENOV'EXPRESS is ideal for treating roofs, façades, walls, terraces and floors. SCALP RENOV'EXPRESS is designed for use on building materials (tile, slate, fibro-cement, shingle, stone, mineral coatings, brick, concrete, roughcast, thick plasticized coatings, wood). SCALP RENOV'EXPRESS allows the elimination in a single operation all kind of blackening from atmospheric pollution.

APPLICATION

1. DILUTION: SCALP RENOV' EXPRESS is ready to use.

2. TOOLS: Equipment in nylon or synthetic fibre: Roller, brush, paintbrush. Can be sprayed with appropriate equipment: manual or electric sprayer and airless spray gun (contact our Sales Department).

3. METHOD: Mix SCALP RENOV'EXPRESS well, then apply to the facade to be treated from bottom to top. Allow to act. No need to rinse unless repainting or water-repellent application, or wet effect beyond 48 hours (see our sales department). Repeat if necessary. For application on lime or hydraulic coatings, consult our sales department.

4. APPLICATION TIME: Instant.

5. APPLICATION TEMPERATURE: From 5 to 50°C. Effectiveness is reduced at extreme temperatures.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE: From 150 to 250 ml /m2 environ.*.

8. STORAGE : Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- Sodium Hypochlorite based aqueous product
- Yellowish liquid
- Density : 1.16 +/- 0.03 g /cm3 at 20°C
- pH : >13
- Not frost resistant
- Flash point : N/A

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect zinc, aluminum, galva, copper, PVC, upholstery, metal or painted surfaces and surrounding vegetation. Protect all surfaces that are not to be cleaned. It is advisable to carry out preliminary tests on all substrates before applying the product.

CAUTION: On hydraulic coatings, crumbling of the plaster may occur. In this case, we recommend thorough remineralization and rinsing of the substrate after application of the product.

2. PROTECTION OF PERSONS: This is a corrosive product. Wear appropriate protective equipment and clothing. Avoid contact with skin and eyes. Wash immediately and abundantly with water in case of contact. Do not inhale fumes and do not mix with acids. Do not pour the product or its waste into rivers or watercourses.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical Data Sheet • April 2025
Page 2/2