

DEROX 320

ODORLESS, AMMONIA-FREE ELASTIC CLEANING PASTE THAT CAN BE PEELED OFF TO REMOVE DIRT, SOOT STAINS, AND DUST. CAN BE APPLIED BOTH INDOORS AND OUTDOORS

PRODUCT BENEFITS



- Peel-off removal
- Ideal for indoor use
- Very easy to apply
- High yield
- Odorless
- No water required



PACKAGING :

- In 15 kg buckets, pallet of 24 x 15 kg

AREAS OF APPLICATION

SCALPNET PEELING This product is used for dry cleaning dirt deposits such as dust, soil deposits, bird droppings, smoke, soot, etc. The product is also effective in cases of superficial soot and dust stains that have penetrated the material with moisture. It is ideal for cleaning the interior and exterior of various surfaces such as brick, concrete, artificial stone made from concrete and cement, limestone, sandstone, chalk, glazed brick, marble, plaster, paint, synthetic materials, metal, etc. Thanks to its high performance, SCALPNET PEELING is particularly suitable for industrial cleaning.

APPLICATION

1. DILUTION: ready to use.

2. TOOLS: Brush or roller or, if necessary, airless spray.

3. METHOD: Mix SCALPNET PEELING thoroughly, then apply a thick layer to the surface to be treated (minimum 1.0 mm). Leave to dry until a uniform transparent film is obtained. Then remove the film by peeling it off.

Note: When cleaning low-porosity surfaces such as marble, it is recommended to follow up with a wet sponge

4. APPLICATION TIME: 2 to 24 hours depending on ambient temperature and humidity. It is sometimes advisable to heat the rooms or ventilate to speed up drying. Note: The maximum application time before removing the film by peeling is one week.

5. APPLICATION TEMPERATURE: From 5 to 50°C. Do not apply the product to heated surfaces and do not expose them to direct heat radiation, as the film will stick and be difficult to remove.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

6. CLEANING OF TOOLS : Tools should be cleaned with water and a small amount of ammonia immediately after use.

7. APPLICATION RATE : From 0.25 to 1 kg/m² depending on the roughness of the substrate.

8. STORAGE : Store the product away from the elements and direct sunlight. Avoid storage at temperatures above 30°C.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- Natural product
- Milky white viscous liquid
- Density: 0.94g ± 0.03g/cm³ at 20°C
- pH : 11
- Not frost resistant, but effects reversible
- Viscosity: 50,000 mPa·s

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES : When cleaning alkali-sensitive surfaces, it is important to bear in mind that this preparation contains a small amount of alkali.

2. PROTECTION OF PERSONS : Wear appropriate and effective protective equipment, avoid contact with skin and eyes. In case of contact, wash immediately and thoroughly with water. Do not breathe vapors and do not mix with acids. Do not discharge the product or its waste into waterways.

Important: The contents of this documentation are based on our experience with the product. We cannot be held responsible for its use in any particular case. In view of the specific characteristics of each surface (wear, alteration of completeness and/or properties, chemical composition, etc.) and to avoid any deterioration of the surface to be treated, it is essential to carry out a test application of Scalp on a small area to be treated, in accordance with the application procedure, to ensure that no alteration has occurred. Professional product: dangerous, observe safety precautions. Wear Personal Protective Equipment (PPE) and consult the Material Safety Data Sheet (MSDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.