



### **SCALP ANTI-STAIN EM**

WATER-REPELLENT, OIL-REPELLENT, FILM-FORMING
WATER-BASED PRODUCT WITH WET EFFECT
IDEAL FOR DRONE APPLICATION



## P PRODUCT BENEFITS

- Highly effective
- Beading effect
- Solvent-free
- Fast, easy penetration into material pores
- Microporous
- Prevents soiling of substrates and limits the formation of micro-organisms
- Wet effect
- VOC-free
- Sprayable: Ideal for drone application = increased safety, time savings, uniform spraying, cost reduction



#### **PACKAGING**

- 200 L barrel
- 20 L: 24 x 20 L pallet
- 5 L: 4 x 5 L pack
- 1 L: 10 x 1 L pack



# A REAS OF APPLICATION

SCALP ANTI-STAIN EM "Restore and Protect" is mainly aimed at restoring and protecting rooftops, floors and terraces. This product is used to give your old materials a restored, new look. It also gives a "wet" look.

SCALP ANTI-STAIN EM protects porous materials from the penetration of water, oil, fat, grease, wine, coffee, tannin etc., mainly on horizontal surfaces like roof tiles, paving, terracotta tiles, interlocking bricks, terracotta flooring, reconstituted stone, marble, concrete, cement and natural stone.

SCALP ANTI-STAIN EM also acts a veritable barrier against the growth of microorganisms on treated surfaces.

# APPLICATION

- 1. DILUTION: Ready to use, do not dilute.
- **2. APPLICATION EQUIPMENT**: Roller, hand sprayer, airless spray gun, Compatible with spray drones
- <u>3. OPERATING PROCEDURE</u>: Thoroughly mix SCALP ANTI-STAIN EM, then saturate the surface to be treated (from bottom to top in the case of a vertical structure). Apply one to two coats, at a 10-minute interval.

Avoid any excess product, as this can cause drippings and leave streaks on the surface. Apply SCALP ANTI-STAIN EM to clean and dry surfaces. If the surface has already been rinsed, wait at least 10 days before applying SCALP ANTI-STAIN EM.

- 4. APPLICATION TIME: Impregnation product. The treatment will be effective once completely dry (8 hours).
- **5. APPLICATION TEMPERATURE**: 5 °C to 50 °C. Effectiveness is reduced at extreme temperatures.
- **6. TOOL CLEANING:** Tools must be cleaned with water straight after use.
- 7. YIELD: Depends on materials and their porosity\*.
- **8. Storage**: Store product in frost-free premises, away from the elements and direct sunlight. Minimum storage temperature: +5 °C. Maximum storage temperature:
- \*Yield information is only provided as a rough guide. This information is useful to work out the amount needed for the project. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

#### **PHYSICO-CHEMICAL FEATURES**

- AFNOR NF T 36-005: Family I Class 61
- Translucent, white liquid
- Density: 1 g ± 0.03 g / cm<sup>3</sup> at 20 °C
- pH: 8
- Keep from freezing
- Flash point: None

## APPLICATION PRECAUTIONS

- 1. PROTECTION OF SURFACES: Protect surfaces that do not need to be treated. (Do not apply to non-absorbent materials like plastics, paints, metal and slates).
- 2. PROTECTION OF PERSONS: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Wear PVC gloves. Wear a helmet with a protective visor for the face during spray application. Wear safety goggles when applying with a roller or brush. Wear suitable overalls (waterproof).

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and / or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs. Professional product: dangerous, follow application precautions. Wear personal protective equipment (PPE) and refer to the safety data sheet (SDS).





