

SCALPFUGE COLOR

WATER-REPELLING, MINERALISING AND STAIN-RESISTING TINTED RESTORER FOR ROOFTOPS, FAÇADES AND WALLS – AVAILABLE IN 11 SHADES



PRODUCT BENEFITS



- 4-in-1 ready-to-use product
- Waterproofs, mineralises and restores concrete by tinting and protecting it against stains
- Effectively protects against the growth of micro-organisms
- Reduces urban soiling
- Limits the disintegration of rooftops as a result of freezing / thawing
- Beading effect
- Does not contain VOC's
- Indoor/outdoor



PACKAGING :

- 5 L two-pack, 96 x 5 L pallet (pack of 4 x 5 L units)

AREAS OF APPLICATION

SCALPFUGE COLOR is an innovative product that restores rooftops, façades, walls and floors.

It is water-repellent and non-film forming, protecting treated surfaces against water ingress and stains, preventing urban soiling, the growth of micro-organisms and disintegration caused by freezing / thawing.

SCALPFUGE COLOR is microporous and mineralising: it impregnates and tints the surface, while respecting its mineral nature, and consolidates it for a reinforced structure. It is specially designed to be applied to concrete, roof tiles, slates, interlocking bricks etc.

Available in 11 shades: WHITE, PEARL GREY, ANTHRACITE, ECRU, OCHRE, SIENNA, ORIENTAL RED, BRICK RED, FLAME RED, SLATE AND "WET EFFECT" COLOURLESS. SCALPFUGE COLOR is a very high-end, multi-purpose product.



APPLICATION

1. DILUTION: Ready to use.

2. APPLICATION EQUIPMENT: Roller, airless spray gun.

3. OPERATING PROCEDURE: Thoroughly mix the SCALPFUGE COLOR colourless base (Part A) and colourant (Part B).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Pour the colourant (Part B) into the base (Part A) and mix well. Apply product from bottom to top to the clean and dry surface to be treated. Apply two coats, at least one hour apart. Avoid any excess product, as this can cause drippings and streaks on the surface once dry.

If the surface was rinsed beforehand, wait a minimum of 10 days before applying SCALPFUGE COLOR.

DRYING: (varies based on weather conditions and the type of structure)

- 25 minutes to the touch.
- 5 to 6 hours for moderate foot traffic.
- 1 day before road traffic can resume.
- 3 days to benefit from the mineralising and consolidating effects.

4. APPLICATION TEMPERATURE: Minimum application temperature: 5 °C. Do not apply in direct sunlight.

5. TOOL CLEANING: Tools must be cleaned with water straight after use.

6. YIELD: 6 to 8 m² per litre, depending on the porosity of the surface*.

7. STORAGE: Store product in frost-free premises, away from the elements and direct sunlight. Do not store at temperatures < 0°C.

*Yield information is only provided as a rough guide. This information is useful to work out the amount needed for the project. This information is in no way contractual. The exact quantity of product to be applied can only be established through tests, based on the different surfaces to be treated.

PHYSICO-CHEMICAL FEATURES

- | | |
|--|----------------------|
| • Aqueous solution that works by impregnation. | • pH: 7 |
| • Colourless base + tint | • Keep from freezing |
| • Density at 1.0 g ± 0.03 g / cm ³ at 20 °C | • Flash point: None |

A APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces that will not be waterproofed (glass, PVC etc.).

2. PROTECTION OF PERSONS: Contains a biocidal substance, a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one methyl-2H-isothiazol-3-one (3:1). Wear gloves and protective equipment during application: water-repellent overalls, PVC gloves; for spray application: a helmet with a protective visor; for roller application: safety goggles. In the event of skin irritation or rash, wash thoroughly with water and see a doctor.

Important: The contents of this document stem from our experience with the product. We cannot be held liable as far as its use is concerned in every individual case. Given the particular characteristics of each surface (wear and tear, alteration of the entire surface and / or its properties, chemical composition etc.), and to avoid any damage to the surface to be treated, it is essential that the Scalp product be tested on a small area to be treated, by following the procedure for application, in order to ensure that no alteration occurs. Professional product: dangerous, follow application precautions. Wear personal protective equipment (PPE) and refer to the safety data sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.