

SCALP ANTI-TACHES 07

HIGH PERFORMANCE WATER REPELLENT, OIL REPELLENT
- NON-FILM FORMING IN WATER PHASE WITH ACRYLIC
FLUORINATED RESIN BASE
IDEAL FOR DRONE APPLICATION



PRODUCT BENEFITS

- BBRI-tested performance
- Highly effective
- Beading effect
- Silicone-free, solvent-free, odorless
- Effective against graffiti
- Fast, easy penetration into material pores
- Microporous
- pH neutral
- Prevents soiling of substrates and limits the formation of micro-organisms
- VOC-free
- Sprayable: Ideal for drone application = increased safety, time savings, uniform spraying, cost reduction



PACKAGING :

- 20 L : pallet of 24 X 20 L
- 5 L : carton of 4 X 5 L
- 1 L : carton of 10 X 1 L



AREAS OF APPLICATION

SCALP ANTI-TACHES 07 is designed to protect facades, walls, all vertical surfaces, floors and terraces. It is used to protect porous materials against the penetration of water, oil, grease, sludge, wine, coffee, tannin, etc. For use on horizontal and vertical surfaces such as flagstones, terracotta tiles, interlocking paving stones, terracotta tiles, reconstituted stone, marble, concrete, cement, natural stone and wood. Ideal for bluestone.

APPLICATION

- 1. DILUTION:** Ready to use, never dilute.
- 2. TOOLS:** Roller, manual sprayer, airless spray gun, Compatible with spray drones
- 3. METHOD:** Mix SCALP ANTI-TACHE 07 well then apply to the surface to be treated (from the base upwards in the case of a vertical surface). Apply one or two coats at 10-minute intervals. Avoid overuse of the product, which could leave coloured traces on the surface. Apply SCALP ANTI-TACHE 07 on clean and preferably dry surfaces.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

4. APPLICATION TIME: N/A SCALP ANTI-TACHE 07 permeates the surface thoroughly. The treatment will be effective immediately on complete drying of SCALP ANTI-TACHE 07 (several hours).

5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures.

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE: According to materials and their porosity.*

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|---|---|
| <ul style="list-style-type: none">• Water based product• Transparent, yellowish liquid• Density : 1 +/- 0.03 g /cm3 at 20°C | <ul style="list-style-type: none">• pH : 7, neutral• Not frost resistant• Flash point : N/A |
|---|---|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces not to be treated. (Do not apply to non-absorbent materials such as plastic, paint, metal or slate).

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, wash immediately with water. Wear PVC gloves. Wear helmet with face shield for spray application. Wear goggles for roller or brush application. Wear suitable coveralls (waterproof).

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.