

WATER-REPELLENT / OIL-REPELLENT RANGE

SCALPFUGE PS 86

HIGH-END WATER REPELLENT BASED ON NANOTECHNOLOGY
BASED ON POLYSILOXANES AND SILANES



P PRODUCT BENEFITS

- Very high-end product
- Very pronounced beading effect
- Does not alter the color of the substrate
- Microporous, facilitating the free exchange of water vapor
- Sprayable
- Quick and easy impregnation into the pores of materials



PACKAGING :

- 30 litres: pallet of 20 X 30L

A AREAS OF APPLICATION

Scalpfuge PS 86 is designed for waterproofing porous substrates such as concrete, stone, brick, hydraulic coatings, cement, etc.

A APPLICATION

1. DILUTION: Ready to use, do not dilute.

2. TOOLS: Natural fiber roller, manual sprayer.

3. METHOD: Clean, dry, and dust the walls before applying the product. Mix SCALPFUGE PS 86 thoroughly, then apply it to the surface to be treated from bottom to top until the surface is completely saturated. Repeat the operation a second time after approximately 10 minutes ("wet on wet" application). Avoid overloading the product, as this may cause dripping and leave marks on the surface. Apply the product to clean, dry surfaces. If the surface has been rinsed beforehand, wait at least 10 days before applying the product.

4. APPLICATION TIME: This is an impregnation product. The water repellency will be effective as soon as the solvents have evaporated (approximately 72 hours later).

5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures.

6. CLEANING OF TOOLS : Tools should be cleaned with white spirit immediately after use.



SCALP[®]
SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.

7. APPLICATION RATE: Depends on materials and their porosity.*: approximately 300g/m² for both layers*.

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|--|---|
| <ul style="list-style-type: none">• Solvent-based product• Flash point: 36°C open cup• Density at 0.78g ± 0.03g/cm³ at 20°C | <ul style="list-style-type: none">• pH: None• Frost resistant• AFNOR NF T 36-005: Family I, Class 10c |
|--|---|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Do not apply SCALPFUGE PS 86 to organic coatings (RPE, RSE paints, etc.). Protect surfaces that are not to be waterproofed (glass, PVC, etc.).

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In case of contact, wash immediately with water. Work in a well-ventilated area; do not smoke. Wear PVC gloves. Wear a helmet with a protective face shield when using a spray. Wear protective goggles when applying with a roller or brush. Wear suitable (waterproof) overalls.

Important: The content of this documentation is based on our experience with the product. We cannot be held liable for its use in each specific case. Given the specific characteristics of each surface (wear, alteration of integrity and/or properties, chemical composition, etc.) and to avoid any damage to the surface to be treated, it is essential to test the Scalp product on a small area of the surface to be treated, following the application procedure, to ensure that there is no alteration. Professional product: dangerous, follow the precautions for use. Wear Personal Protective Equipment (PPE) and consult the Safety Data Sheet (SDS).



SCALP SAS, an EcoVadis-certified company - the certification is awarded to the company, not the product.

SCALP[®] SAS

SCALP is a French family-owned company that manufactures cleaning, protective, and maintenance products, specializing in the construction industry for over 70 years.