

SCALPFUGE 35

HIGH-END WATER REPELLENT - PRONOUNCED PEARL EFFECT
IDEAL FOR FINISHING OR RENOVATING FACADES, WALLS AND ROOFS
TRANSPARENT, NON-FILM-FORMING PRIMER
IDEAL FOR DRONE APPLICATION



PRODUCT BENEFITS

- CSTC-tested performance
- European efficiency approval, Class A: excellent efficiency.
- Very pronounced beading effect
- Limits frost damage
- Microporous
- Does not change the appearance or porosity of the substrate
- Odorless
- Fast, easy penetration into material pores
- Solvent- and silicone-free
- Prevents soiling of roofs and limits the formation of micro-organisms
- Sprayable
- Low VOC content: 1mg/L



PACKAGING :

- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres



AREAS OF APPLICATION

SCALPFUGE 35 is mainly designed for the protection of walls and façades as well as roofing and all porous materials. It is used for the waterproofing of hydraulic coatings, stones, bricks, marbles, concrete, tiles, slates and fibrocement.

APPLICATION

1. DILUTION: Ready to use, do not dilute.

2. TOOLS: Roller, manual sprayer, airless spray gun, Compatible with spray drones

3. METHOD: Thoroughly mix SCALPFUGE 35, then apply to the surface to be treated, working bottom to top until the surface is saturated. Apply 2 coats, at 10-minute intervals. Avoid using excess product which can lead to drippings and leave streaks on the surface. Apply SCALPFUGE 35 on clean and dry surfaces.

4. APPLICATION TIME: SCALPFUGE 35 is an impregnating product. Waterproofing will take effect as soon as SCALPFUGE 35 has completely dried (one to several hours).

5. APPLICATION TEMPERATURE: From 5 to 50°C. Efficacy is reduced at extreme temperatures.



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

6. CLEANING OF TOOLS : Clean tools in water immediately after use.

7. APPLICATION RATE: Depends on materials and their porosity.*

8. STORAGE: Store the product in a frost-free location where it is protected from the weather and away from direct sunlight.

* Coverage areas are provided for information only and can be used to assess a project. They are in no way contractual; only tests can define the actual amount of product required depending on the surface to be treated.

PHYSICOCHEMICAL PROPERTIES

- | | |
|---|---|
| <ul style="list-style-type: none">• Aqueous product• White liquid• Density : 1 +/- 0.03 g /cm³ at 20°C | <ul style="list-style-type: none">• pH : 7 (neutral)• Keep away from extreme cold• Flash point : N/A• AFNOR NF T 36-005: Family 1, Class 10c |
|---|---|

APPLICATION PRECAUTIONS

1. PROTECTION OF SURFACES: Protect surfaces that will not be waterproofed (glass, PVC etc.).

2. PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. In the event of contact, immediately wash with water. Wear PVC gloves. Wear a helmet visor to shield the face while spraying. Wear safety goggles when applying with a roller or brush. Wear suitable overalls (waterproof).

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand. See the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.