





# FORMULATED FROM BIOSOURCED RAW MATERIALS RENEWABLE WATER-BASED COLORLESS ANTI-GRAFFITI PROTECTION MATT FINISH



## P PRODUCT BENEFITS

- Water-based
- Biosourced raw material
- Easy to use: sprayable product
- Odorless and solvent-free
- Colorless, matt finish
- High UV resistance: does not yellow
- Suitable for indoor and outdoor use
- 2-in-1 product: anti-graffiti and waterrepellent protection
- Microporous



### **PACKAGING:**

- 20L, pallet of 24 x 20L
- 5L, box of 4 x 5L



## REAS OF APPLICATION

ANTI-GRAFF R EKO'R is a water-based, colorless, sacrificial anti-graffiti protection. It protects all types of surfaces such as stone, concrete, cement, wood, hydraulic render, against graffiti and water infiltration. Suitable for both outdoor and indoor use.

SURFACES

# APPLICATION

DILUTION: Ready to use, do not dilute.

**APPLICATION TOOLS:** Roller, airless.

<u>INSTRUCTIONS:</u> Homogenize well before applying two crossed coats at 2-hour intervals (depending on temperature) on a clean and dry surface. Avoid product overload.

<u>REMOVE GRAFFITL:</u> With hot water at min. 90°C and 90 bars pressure. The protection disappears and must be renewed.

<u>APPLICATION TIME</u>: Effective after approx. 2 hours (depending on climate and substrate).

<u>APPLICATION TEMPERATURE</u>: From 5°C to 50°C. Reduced efficiency at extreme temperatures. Do not apply below 5°C.

**CLEANING OF TOOLS**: With hot water immediately after use.

<u>APPLICATION RATE</u>: 150 to 200 g/m<sup>2\*</sup> depending on substrate porosity. <u>STORAGE</u>: Store frost-free, protected from bad weather and direct sunlight.



and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.

Technical sheet • April 2025

\*The yield data are given for information purposes only. These figures allow an estimate of project costs. They are not contractual; only tests can determine the exact quantity of product to be applied depending on the different substrates to be treated.

#### PHYSICO-CHEMICAL CHARACTERISTICS

Very low odor

· Milky liquid appearance

Density: 1.05g ± 0.03g/cm³ at 20°C

pH: 7

Sensitive to frost

Flash point: None

## A PPLICATION PRECAUTIONS

**1. PROTECTION OF SURFACES**: Avoid projection on unprotected substrates. Do not apply on untreated metallic surfaces.

**2.** PROTECTION OF PERSONNEL: Avoid contact with eyes and skin. Wear PVC gloves and protective goggles. In case of contact, rinse with water.

Important: The content of this document is based on our experience with the product. It does not bind our responsibility regarding its use in each particular case. Considering the specificities of each substrate (wear, alteration of integrity and/or properties, chemical composition, etc.) and to avoid any damage to the treated surface, it is essential to carry out a test of the Scalp product on a small area following the application procedure to ensure the absence of alteration. Professional product: dangerous, follow the precautions for use. Wear Personal Protective Equipment (PPE) and consult the Safety Data Sheet (SDS).



SCALP is a French family-owned business and manufacturer of cleaning, protection and treatment solutions, with over 65 years as a construction-industry specialist.



